




® **ATLAS WIRE LLC.**  
 1601 Glenlake Av.  
 Itasca, ILLINOIS 60143  
 (847) 678-1210  
 (847) 678-1281  
 www.atlaswirecorp.com



## MATERIAL SPECIFICATION SHEET

**#10 37/26 TC .045" PVC**  
**RoHS Compliant**  
**MIL-W-76D TYPE HWP**  
**80c - 600 VOLTS**

**CONDUCTOR:** #10 37/26 TINNED COPPER 1/2"  
 NOMINAL O.D. .108"  
 APPROXIMATE CIRCULAR MILL AREA 9,401  
 WEIGHT PER THOUSAND FEET 29.31#  
 BASIC SPECIFICATION ASTM B-8  
 ASTM B-286

**PVC:** TEMPERATURE RATING 105c  
 VOLTAGE RATING 600 VOLTS  
 ELONGATION 320% AVG.  
 SPECIFIC GRAVITY 1.34  
 DUROMETER (SHORE) 85 (A)  
 TENSILE STRENGTH 2450 PSI AVG  
 SPARK TESTED 12,500 VOLTS  
 OXYGEN INDEX 25  
 BRITTLE POINT -25c  
 FINISHED O.D. .198"  
 WEIGHT PER 1,000 FEET 42.32#

www.atlaswirecorp.com