



® **ATLAS WIRE LLC.**
 1601 Glenlake Av.
 Itasca, ILLINOIS 60143
 (847) 678-1210
 (847) 678-1281
 www.atlaswirecorp.com



Atlas Wire, LLC
 Registered to ISO9001:2015
 and IATF 16949:2016
 Itasca, IL 60143
 Reference No. 10000854



Atlas Wire, LLC
 Registered to ISO9001:2015
 Tucson, AZ 85714
 Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#12 19/25 TC .017" PVC .004" NYLON
RoHS COMPLIANT
MIL-16878/18 TYPE CN
105c - 1,000 VOLTS

CONDUCTOR:	#12 19/25 TINNED COPPER 1-1/4" NOMINAL O.D. .090" APPROXIMATE CIRCULAR MILL AREA 6,088 WEIGHT PER THOUSAND FEET 18.80# BASIC SPECIFICATION ASTM B-8 ASTM B-286
PVC:	TEMPERATURE RATING 105c VOLTAGE RATING 1000 VOLTS ELONGATION 330% AVG. SPECIFIC GRAVITY 1.32 DUROMETER (SHORE) 91 (A) TENSILE STRENGTH 2450 PSI AVG SPARK TESTED 8,500 VOLTS OXYGEN INDEX 28 BRITTLE POINT -24c FINISHED O.D. .124" WEIGHT PER 1,000 FEET 22.24#
NYLON:	ELONGATION 300% TENSILE STRENGTH 7400 PSI @ 50% RELATIVE HUMIDITY SPECIFIC GRAVITY 1.13 OVERALL DIAMETER .132" WEIGHT PER M FEET 22.95#
REVISION:	MIL-DTL-16878G - PRINT REQUIRED*

* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED
 PLEASE CALL THAT OUT AT TIME OF ORDER.

MEETS ALL REQUIREMENTS LISTED ON THE MIL-DTL-16878/18B DETAIL SPECIFICATION SHEET WITH THE EXCEPTION OF ATLAS CONDITIONING FOR THE HEAT RESISTANCE TEST AT 136c.

www.atlaswirecorp.com

Revision 09/29/2023