



® **ATLAS WIRE LLC.**  
 1601 Glenlake Av.  
 Itasca, ILLINOIS 60143  
 (847) 678-1210  
 (847) 678-1281  
 www.atlaswirecorp.com



## MATERIAL SPECIFICATION SHEET

**#18 7/26 TC .010" PVC .003" NYLON**  
**RoHS COMPLIANT**  
**MIL-16878/17 TYPE BN**  
**105c - 600 VOLTS**

<b>CONDUCTOR:</b>	#18 7/26 TINNED COPPER 3/4"	
	NOMINAL O.D.	.048"
	APPROXIMATE CIRCULAR MILL AREA	1.779
	WEIGHT PER THOUSAND FEET	5.56#
	BASIC SPECIFICATION	ASTM B-8 ASTM B-286
<b>PVC:</b>	TEMPERATURE RATING	105c
	VOLTAGE RATING	600 VOLTS
	ELONGATION	300% AVG.
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	47 (D)
	TENSILE STRENGTH	3000 PSI AVG
	SPARK TESTED	5,700 VOLTS
	OXYGEN INDEX	25
	BRITTLE POINT	-29c
	FINISHED O.D.	.068"
	WEIGHT PER 1,000 FEET	6.65#
<b>NYLON:</b>	ELONGATION	300%
	TENSILE STRENGTH	7400 PSI @ 50%
		RELATIVE HUMIDITY
	SPECIFIC GRAVITY	1.13
	OVERALL DIAMETER	.076"
	WEIGHT PER M FEET	6.95#
<b>REVISION:</b>	MIL-DTL-16878G	- PRINT REQUIRED*

\* OUR STANDARD IS PRINTED, IF NO PRINTING IS PREFERRED  
 PLEASE CALL THAT OUT AT TIME OF ORDER.

MEETS ALL REQUIREMENTS LISTED ON THE MIL-DTL-16878/17B DETAIL SPECIFICATION SHEET WITH THE EXCEPTION OF ATLAS CONDITIONING FOR THE HEAT RESISTANCE TEST AT 136c.

www.atlaswirecorp.com

Revision 09/29/2023