



ATLAS WIRE LLC.
9525 RIVER STREET
SCHILLER PARK, ILLINOIS 60176
(847) 678-1210
(847) 678-1281 FAX
www.atlaswirecorp.com



Atlas Wire, LLC
Registered to ISO9001 and TS16949
Schiller Park, IL 60176
Reference No. 10000854
Tucson, AZ 85714
Reference No. 10003647

MATERIAL SPECIFICATION SHEET

#20 10/30 TC .010" PVC
RoHS COMPLIANT
UL AWM STYLE 1061 80c-300v or
UL AWM STYLE 10002 105c-300v or
CSA AWM 105c-300v CLASS I A/B SR PVC

CONDUCTOR:	#20 10/30 TINNED COPPER 1/2" BUNCHED NOMINAL O.D.	.038"
	APPROXIMATE CIRCULAR MILL AREA	1,000
	WEIGHT PER THOUSAND FEET	3.20#
	BASIC SPECIFICATION	ASTM B-174
PVC:	TEMPERATURE RATING	105c
	VOLTAGE RATING	300
	ELONGATION	300% AVERAGE
	SPECIFIC GRAVITY	1.34
	DUROMETER (SHORE)	60 (D)
	TENSILE STRENGTH	3210 PSI
	OXYGEN INDEX	28
	BRITTLE POINT	-8c
	SPARK TESTED	3,500 VOLTS
	FINISHED O.D.	.058"
	WEIGHT PER THOUSAND FEET	4.107#
USE:	INTERNAL WIRING IN ELECTRIC BOOKKEEPING, ACCOUNTING, TIME RECORDING MACHINES, OR ELECTRONIC EQUIPMENT IF WITHIN A CHASSIS OR PROTECTED FROM MECHANICAL INJURY.	

info@atlaswirecorp.com

Revision 02-22-16